

CONDENSATE RECIRCULATING SYSTEM

Caron's 2nd generation Universal Condensate Recirculating System acts as a water delivery system for use with any Caron humidity controlled chamber. The CRSY102 was designed so you can utilize tap water, eliminating the need to purchase more expensive water purification systems or maintain a supply of distilled/deionized water.

The need for a floor drain is also eliminated because the CRSY102 recycles chamber condensate. The CRSY102 maintains and controls water purity between 100-125 k Ω -cm. Precise water purity control enhances the chamber's cleanliness and maximizes the life of components in the humidification system. With the optional CRSYKIT, the Universal Condensate Recirculating System can supply water for any two Caron humidity controlled chambers, even in high water usage situations.



STANDARD FEATURES

- The Universal Condensate Recirculating System is environmentally friendly, minimizing water consumption and lowering utility and installation expenses.
- The DI cartridge and carbon filter remove minerals, chloramides, chloramines and sediments from the water, eliminating the build-up of scale deposits that can damage components exposed to water.
- The antimicrobial action of our metal stick works to prevent bacteria, molds and fungi for a contamination-free water source.
- The large reservoir is backlit for at-a-glance monitoring of the water level. The "Add Water" indicator light provides you with an additional visual indicator of when to add water.
- "Replace Filters" indicator light alerts you when to change water filters so that proper water purity is maintained.
- Finger latches on both full-length side access panels allow quick access to replace filters and for convenient servicing.

STANDARD FEATURES *continued*

- The single switch operation and automatic air purge minimize and simplify user interaction.
- Front/rear handles and casters provide easy mobility for installation and service.
- The optional UV germicidal lamp deactivates microorganisms including bacteria, molds, protozoa, viruses and yeasts for contamination-free water.

SPECIFICATIONS

MODEL	CRSY102-1	CRSY102-4
Water Purity*	100-125 kΩ-cm	
Exterior Dimensions	14" W x 26.5" D x 26.6" H (35.5 cm W x 67.3 cm D x 67.7 cm H)	
Exterior Material	Durable powder coated metal	
Water Reservoir	7 gallons (26.5 liters)	
Electrical	115V, 60 Hz, 5 Amp (NEMA 5-15P plug)	230V, 50/60 Hz, 2 Amp (CEE 7/7 plug)
Weight, Shipping	125 lbs (57 kg)	200 lbs (91 kg)
Weight, Empty	84 lbs. (38 kg)	

*Water purity measured internally.

Specifications are subject to change without notice.

OPTIONAL ACCESSORIES

STOCK NO.	DESCRIPTION
CRSYKIT	Fitting and tubing kit for connection to two chambers
FLTR101	Replacement Filter Kit for CRSY102. Includes DI cartridge, carbon filter and metal stick.
LGHT601	UV Germicidal Water Purifying Lamp